

## AIRLIE CLASSIC START UP INSTRUCTIONS

Remove the filter from the spa (see page 8 in your user manual).  
Place a hose in the filter box to fill the spa with water (see page 7 in your user manual).  
(Remove the fittings from your hose to prevent them falling into the spas plumbing).

Set your main diverter on the spa to the centre so that both sides of the spas plumbing will fill up with water. Refer to your user manual to locate the main diverter.

Fill the spa until the water level covers the top of the highest jet.

**Note:** It is extremely important that you fill your spa with water and fit the hardcover as soon as the spa is put outside even if your electrician is not coming straight away. The screws to fit your hardcover clips onto the spas cabinet are taped to the packaging on the spa, make sure you locate them before you dispose of the packaging. In the same pack there will be a drain fitting which you will need when it comes time to drain the spa. On the hardcover itself you will find the clips which you need to screw onto the spas cabinet to lock the hardcover down. On one of these clips there will be a small plastic bag attached which will have the keys you will need to lock the cover.

Your hard cover must always be on the spa when not in use, and the spa must always be filled with water. Failure to do this can lead to melting, crazing and discoloration of the spas acrylic from exposure to the sun. This can occur in as little as 10 minutes if your spa is left without water in it. Melting, crazing and discoloration of the spas acrylic is not covered by warranty.

Have a qualified electrician connect the spa to power. The power supply your electrician needs to connect is 10Amp Single Phase with the appropriate sized RCD in your houses metre box. Please refer to page 5 through to page 6 of your user manual.

Once the spa has power connected to it and it is filled with water turn the power on. Never turn the spa on if you do not have it filled with water. Put the spa into Active mode see page 10 of your user manual. Once you are in active mode press Jets 1 see page 11 of your user manual, you should now have water movement within the spa. Wait 5 minutes then press Jets 1 to turn the pump off.

Go to page 12 in your user manual and follow the instructions to set the time of day and the cleaning cycle. Now set your desired temperature following the setting the cycle heating instructions on page 13 of your user manual.

Go to your weekly chemical instructions and balance the spas water.

**FREE SHIPPING ON CHEMICAL ORDERS OVER \$99**

Visit: [www.aquapulsespas.com.au](http://www.aquapulsespas.com.au)